

ULTIMATE SUMP PUMP VACUUM

ATTIX 19 AE Flood Sucker

Collect and discharge nearly one gallon of water per second with the ATTIX 19 AE Flood Sucker. It is the ideal solution for flood restoration companies, abatement contractors, fire departments, hotels, apartment complexes, disaster relief and emergency response teams and municipalities.

The ATTIX Flood Sucker separates solids into a stainless-steel basket inside the canister while liquids are simultaneously discharged through a fire hose.

The powerful discharge pump expels water up to 30 feet vertically and 150 feet horizontally. It can be operated in three modes—vacuum only, pump only, or vacuum and pump.

Where ordinary sump pumps leave up to 1.5 inches of liquid on the ground, the Flood Sucker completely removes liquids, leaving a dry surface behind.

Also includes onboard power receptacle and tool deposit. With its soft start feature, this commercial vac doesn't pull the full amp draw right away to avoid possible breaker problems.



Standard features:

- Accessory storage
- Onboard sump pump
- Rubber cable with wrap hook
- Soft start
- Tool deposit
- Power regulator
- Washable filter screen
- Large wheels
- GFCI power cord

Technical data

Technical data	ATTIX 19 AE
Part number	302001541
Voltage @ 60 Hz (V)	120
Power @ 60 Hz. (W)	1000
Airflow, max. (CFM)	140
Waterlift, max. (In. H ₂ O)	105
Noise level (dB(A)) @ working distance of 3 m	57
Container capacity (gal./L)	19/72
L x W x H (in)	24 x 23 x 38
Shipping weight (lbs.)	97

Standard accessories

Hose (dia. x L) (in. x ft.)	1.5 x 13 (Part #15365)
Discharge hose, 50' lay-flat hoses	PN 7567
Curved wand, stainless steel	PN 46691
Extension tube (2 pieces), stainless steel	PN 107408074
Tube holder	(Part #60609)
Industrial squeegee	(Part #5149)

Nilfisk, Inc.

9435 Winnetka Ave N • Brooklyn Park, MN 55445
Phone: 800-989-2235 • Email: asknilfisk@nilfisk.com

www.nilfisk.us

NILFISK